

FILON[®] ON YOUR SIDE

CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No. FPL CE0120 CPR 09-2013 Rev5 03/2026

1. Unique identification code of the product-type:

CEDR24E

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Type, number and specific product details are provided with the goods on the delivery note.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised Technical Specification, as foreseen by the manufacturer:

Light transmitting single skin GRP sheets for discontinuously rooflight or as the external sheet of a multiple layer assembly.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR:

**Filon Products Limited,
Unit 3 Ring Road
Zone 2 Burntwood Business Park
Burntwood
Staffordshire
WS7 3JQ**

**Tel: 01543 687300
email: sales@filon.co.uk**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2) of the CPR:

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1013:2012 + A1:2014

FILON[®] ON YOUR SIDE

| Essential Characteristics | Performance | Harmonised Technical Specification |
|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|------------------------------------|
| External fire performance | NPD - UK fire ratings declared separately | EN 1013:2012 + A1:2014 |
| Reaction to fire | NPD - UK fire ratings declared separately | |
| Water vapour permeability | 1.5 x 10 ⁻⁵ mg/(m h Pa) | |
| Water / air permeability | Pass | |
| Release of dangerous substances | NPD | |
| Dimensional tolerances | Pass | |
| Shatter properties (safe breakability) as: | | |
| - Small hard body impact resistance | NPD | |
| - Large soft body impact resistance (assembly) | NPD. Performance to ACR(M)001 declared separately in accordance with NA to BS EN 1013 and Rooflight Association NTD03 | |
| Mechanical resistance (deformation behaviour) | NPD | |
| Flexural tensile strength | NPD | |
| Resistance to fixings | See manufacturer's fixing instructions | |
| Durability, as variation (after ageing): | | |
| - of yellowness index | NPD | |
| - of the light transmission | NPD | |
| - on flexural strength for: > flexural strength, and > flexural modulus | NPD NPD | |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:



Mark Wilcox
Managing Director

Filon Products Limited, Burntwood, 31/03/2026