

CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No. FPL CE0150 CPR 09-2013 Rev4 03/2025

1. Unique identification code of the product-type:
CE30
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
Type, number and specific product details are provided with the goods on the delivery note.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised Technical Specification, as foreseen by the manufacturer:
Light transmitting single skin GRP sheets for discontinuously laid internal rooflight for buildings.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR:
**Filon Products Limited,
Unit 3 Ring Road
Zone 2 Burntwood Business Park
Burntwood
Staffordshire
WS7 3JQ

Tel: 01543 687300
email: sales@filon.co.uk**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2) of the CPR:
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 4
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
EN 1013:2012 + A1:2014

8. Declared performance:

Essential Characteristics	Performance	Harmonised Technical Specification
External fire performance	NPD - UK fire ratings declared separately	EN 1013:2012 + A1:2014
Reaction to fire	NPD - UK fire ratings declared separately	
Water vapour permeability	1.5 x 10 ⁻⁵ mg/(m h Pa)	
Water / air permeability	Pass	
Release of dangerous substances	NPD	
Dimensional tolerances	Pass	
Shatter properties (safe breakability) as:		
- Small hard body impact resistance	NPD	
- Large soft body impact resistance (assembly)	NPD. Performance to ACR(M)001 declared separately in accordance with NA to BS EN 1013 and Rooflight Association NTD03	
Mechanical resistance (deformation behaviour)	NPD	
Flexural tensile strength	NPD	
Resistance to fixings	See manufacturer's fixing instructions	
Durability, as variation (after ageing):		
- of yellowness index	NPD	
- of the light transmission	NPD	
- on flexural strength for: > flexural strength, and > flexural modulus	NPD NPD	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:



Mark Wilcox
Managing Director

Filon Products Limited, Burntwood, 05/03/25

Filon Products Limited

Unit 3, Ring Road, Zone 2, Burntwood Business Park

Burntwood, Staffordshire WS7 3JQ, England

Tel: +44 (0)1543 687300

Email: sales@filon.co.uk Website: www.filon.co.uk